

# Gear pump

## TG-47G-PU-DB4-KA, 24V



### Characteristics / Specification

MODEL	47G-PU-DB4
VOLTAGE	24V
RATED DELIVERY PRESSURE (MPa)	0.05
RATED DELIVERY PRESSURE (kg/cm <sup>2</sup> )	0.5
RATED DELIVERY FLOW (ml/min), MIN	400
RATED CURRENT (mA), MAX	400

(Representative value)

## TG-85E-PU-DB4-KA, 24V



### Characteristics / Specification

MODEL	85E-PU-DB4
VOLTAGE	24V
RATED DELIVERY PRESSURE (MPa)	0.05
RATED DELIVERY PRESSURE (kg/cm <sup>2</sup> )	0.5
RATED DELIVERY FLOW (ml/min), MIN	270
RATED CURRENT (mA), MAX	350

(Representative value)

## TG-85E-PU-EB4-KA, 24V



### Characteristics / Specification

MODEL	85E-PU-EB4
VOLTAGE	24V
RATED DELIVERY PRESSURE (MPa)	0.1
RATED DELIVERY PRESSURE (kg/cm <sup>2</sup> )	1
RATED DELIVERY FLOW (ml/min), MIN	500
RATED CURRENT (mA), MAX	500

(Representative value)

## TG-30S-PU-DB-KA, 24V



### Characteristics / Specification

MODEL	30S-PU-DB
VOLTAGE	24V
RATED DELIVERY PRESSURE (MPa)	0.1
RATED DELIVERY PRESSURE (kg/cm <sup>2</sup> )	1
RATED DELIVERY FLOW (ml/min), MIN	800
RATED CURRENT (mA), MAX	1000

(Representative value)

## TG-30S-PU-EB-KA, 24V



### Characteristics / Specification

MODEL	30S-PU-EB
VOLTAGE	24V
RATED DELIVERY PRESSURE (MPa)	0.1
RATED DELIVERY PRESSURE (kg/cm <sup>2</sup> )	1
RATED DELIVERY FLOW (ml/min), MIN	1300
RATED CURRENT (mA), MAX	1300

(Representative value)